

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number
WO 2003/089784 A3


- (51) International Patent Classification⁷: **F02P 3/02**
- (74) Agent: **COHEN, Jerry; Perkins, Smith & Cohen, LLP**,
One Beacon Street, Boston, MA 02108 (US).
- (21) International Application Number:
PCT/US2003/012057
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.
- (22) International Filing Date: 19 April 2003 (19.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/374,019 19 April 2002 (19.04.2002) US
60/432,161 10 December 2002 (10.12.2002) US
60/450,217 25 February 2003 (25.02.2003) US
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): **COM-
BUSTION ELECTROMAGNETICS, INC.** [US/US]; 32
Prentiss Road, Arlington, MA 02476 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **WARD, Michael, A.,
V.** [US/US]; c/o Combustion Electromagnetics, Inc., 32
Prentiss Road, Arlington, MA 02476 (US).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: **IMPROVED MCU BASED HIGH ENERGY IGNITION**



(57) Abstract: A high energy inductive coil-per-plug ignition system operating at a higher voltage V_c than battery voltage V_b by use of boost-type power converter (1), using high energy density low inductance coils T_i which are further improved by partial encapsulation of the coils and by use of biasing magnets (120) in the large air gaps in the core to increase coil energy density, the coils connected to capacitive type spark plugs, with improved halo-disc type firing ends, by means of improved suppression wire (78), the system operated and controlled by a micro-controller (8) to generate and control the coil charge time T_{ch} , the sequencing the spark firing, and other control features including finding the firing cylinder by simultaneous ignition firing and sensing during engine cranking, to provide a highly controlled and versatile ignition system capable of producing high energy flow-coupling ignition sparks with relatively fewer and smaller parts.

BEST AVAILABLE COPY